



DONGGUAN JIUSHENG MACHINERY CO., LTD.

271, RENZHOU RD, DONGGUAN, GUANGDONG, CHINA

<http://www.dgchiller.com>; Email: cnjiusheng@dgchiller.com

WhatsApp: +86 158-1820-1390

Three-in-one Dehumidification Dryer Parameter

Model		JSCSJ-50	JSCSJ-80	JSCSJ-120	JSCSJ-150	JSCSJ-200	JSCSJ-300	JSCSJ-400	JSCSJ-500	JSCSJ-700	JSCSJ-1000
Dehumid air volume	m ³ /HR	50	80	120	150	200	300	400	500	700	1000-1000
Runner size		φ150*200H	φ180*200H	φ250*200H	φ250*300H	φ250*400H	φ350*300H	φ350*400H	φ440*300H	φ440*400H	φ550*400H
Regenerative power	kW	3	3.9	4.5	6	6	8	8	12	14	16
Drying fan	kW	0.4	0.55	0.75	1.5	1.5	2.2	3	5.5	7.5	8.5
Regenerative fan	kW	0.18	0.2	0.4	0.4	0.4	0.55	0.55	1.1	1.5	2.2
Air inlet and outlet diameter	Inch	2	2	2.5	2.5	2.5	3	3	4	4	5
Power Supply		3PH-380V-50HZ									
Width	mm	600	600	650	650	650	800	800	900	900	1000
Depth	mm	700	700	850	900	900	1100	1100	1100	1200	1300
Height	mm	1450	1450	1550	1760	1760	1800	1800	2050	2050	2050
Cooling water port		DN25	DN25	DN25	DN25	DN25	DN25	DN25	DN25	DN25	DN25
Total power	kW	3.58	9.63	5.65	7.9	7.9	10.75	11.55	18.6	23	26.7